:

Version 1.0	Revision Date 04/14/20	15 Print Date 10/14/2015
SECTION 1. PRODUCT AND	COMPANY IDENTIFICATION	
Material name	: A06449 BRDWLK AP CI	LNR BWK342A 20N19
Material number	: 00000000001041290	
Manufacturer or suppli	er's details	
Company	:	
Address	:	

Emergency telephone numbers For SDS Information : For a Medical Emergency : For a Transportation : Emergency :

Note: This product is labeled as a consumer product in accordance with the United States Consumer Product Safety Commission regulations. The warnings presented below in this Safety Data Sheet (SDS) comply with the 2012 OSHA Hazard Communication Standard (GHS - Globally Harmonized System of Classification and Labeling). The requirements for the labeling and warnings of consumer products may differ from those required for GHS based hazard communication.

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Telephone

Appearance	Aerosol containing a liquefied gas	
Colour	white	
Odour	mint-like	
GHS Classification		
Gases under pressure	: Liquefied gas	
GHS Label element		
Hazard pictograms		
Signal word	: Warning	
Hazard statements	: H280 Contains gas under pressure; may explode if heated.	
Precautionary statements	: Storage: P410 + P403 Protect from sunlight. Store in a well-ventilated place.	

Potential Health Effects

Version 1.0	Revision Date 04/14/2015	Print Date 10/14/2015	
Carcinogenicity:			
IARC	No component of this product presen equal to 0.1% is identified as probabl human carcinogen by IARC.		
ACGIH	Confirmed animal carcinogen with unknown relevance to humans 2-butoxyethanol 111-76-2		
OSHA	No component of this product presen equal to 0.1% is identified as a carcir carcinogen by OSHA.	t at levels greater than or	
NTP	No component of this product present equal to 0.1% is identified as a know by NTP.		

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous components

Chemical Name	CAS-No.	Concentration [%]
butane	106-97-8	>= 1 - < 5
2-butoxyethanol	111-76-2	>= 1 - < 5
ethanol	64-17-5	>= 1 - < 5

SECTION 4. FIRST AID MEASURES

General advice	: Do not leave the victim unattended. Show this safety data sheet to the doctor in attendance. Move out of dangerous area.
If inhaled	 If unconscious place in recovery position and seek medical advice. If symptoms persist, call a physician.
In case of skin contact	 If skin irritation persists, call a physician. Wash off immediately with plenty of water for at least 15 minutes. If on clothes, remove clothes.
In case of eye contact	 Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist. If in eyes, rinse with water for 15 minutes.
If swallowed	 Keep respiratory tract clear. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. DO NOT induce vomiting unless directed to do so by a physician or poison control center.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray jet

Revision Date 04/14/2015	Print Date 10/14/2015
Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical	
: High volume water jet	
: Do not allow run-off from fire fightin courses.	ng to enter drains or water
: Carbon dioxide (CO2) Carbon monoxide Smoke	
:	
Use extinguishing measures that a circumstances and the surrounding	
: Standard procedure for chemical fi Use extinguishing measures that a circumstances and the surrounding	are appropriate to local
ent : Wear self-contained breathing app necessary.	paratus for firefighting if
	 Alcohol-resistant foam Carbon dioxide (CO2) Dry chemical High volume water jet Do not allow run-off from fire fightin courses. Carbon dioxide (CO2) Carbon monoxide Smoke Use extinguishing measures that a circumstances and the surrounding Standard procedure for chemical f Use extinguishing measures that a circumstances and the surrounding Standard procedure for chemical f Use extinguishing measures that a circumstances and the surrounding

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Use personal protective equipment. Ensure adequate ventilation. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	:	Sweep up or vacuum up spillage and collect in suitable container for disposal. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).

SECTION 7. HANDLING AND STORAGE

Advice on safe handling	 Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Dispose of rinse water in accordance with local and national regulations. Always replace cap after use. Do not breathe vapours or spray mist. Take precautionary measures against static discharges.
	Take precadionary measures against static discharges.

Version 1.0	Revision Date 04/14/2015	Print Date 10/14/2015
	Avoid exposure - obtain special in	structions before use.
Conditions for safe storage	 BEWARE: Aerosol is pressurized. Keep away from direct s exposure and temperatures over 50 °C. Do not open by for or throw into fire even after use. Do not spray on flames or red-hot objects. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards. Keep in a dry, cool and well-ventilated place. 	
Materials to avoid	: Store and keep away from bases	and alkalies.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
butane	106-97-8	TWA	800 ppm 1,900 mg/m3	NIOSH REL
		TWA	800 ppm 1,900 mg/m3	OSHA P0
2-butoxyethanol	111-76-2	TWA	20 ppm	ACGIH
		TWA	5 ppm 24 mg/m3	NIOSH REL
		TWA	50 ppm 240 mg/m3	OSHA Z-1
		TWA	25 ppm 120 mg/m3	OSHA P0
ethanol	64-17-5	TWA	1,000 ppm	ACGIH
		TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		TWA	1,000 ppm 1,900 mg/m3	OSHA P0

Components with workplace control parameters

Biological occupational exposure limits

Component	CAS-No.	Control	Biological	Sampling	Permissible	Basis
		parameters	specimen	time	concentration	
2-BUTOXYETHANOL	111-76-2	Butoxyacetic acid (BAA)	Urine	End of shift (As soon as possible after exposure ceases)	200 mg/g	ACGIH BEI
Remarks: Creatinine	1					1

Personal protective equipment

Respiratory protection

: Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates

Version 1.0	Revision Date 04/14/2015	Print Date 10/14/2015	
	that exposures are within recomme	ended exposure guidelines.	
Hand protection Remarks	: The suitability for a specific workpla with the producers of the protective		
Eye protection	: Ensure that eyewash stations and the workstation location. Tightly fitting safety goggles		
Skin and body protection	: impervious clothing Choose body protection according concentration of the dangerous sub		
Hygiene measures	: When using do not eat or drink. When using do not smoke. Wash hands before breaks and at	the end of workday.	

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	Aerosol containing a liquefied gas
Colour	:	white
Odour	:	mint-like
Odour Threshold	:	no data available
рН	:	no data available
Melting point/freezing point	:	no data available
Boiling point	:	not applicable
Flash point	:	
		not applicable
Evaporation rate	:	no data available
Upper explosion limit	:	no data available
Lower explosion limit	:	no data available
Vapour pressure	:	not applicable
Relative vapour density	:	no data available
Density	:	no data available
Solubility(ies)		
Water solubility	:	soluble
Solubility in other solvents	:	not determined
Partition coefficient: n- octanol/water	:	no data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	no data available
Viscosity		

Version 1.0	Revision Date 04/14/2015	Print Date 10/14/2015
Viscosity, kinematic	: no data available	

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. No decomposition if stored and applied as directed.
Conditions to avoid	: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Incompatible materials	: Alkali metals Copper
Hazardous decomposition products	: Amines Carbon oxides Nitrogen oxides (NOx)

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:	
Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	 Acute toxicity estimate : > 10 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Components:	
butane:	
Acute inhalation toxicity	: LC50 mouse: 1,237 mg/l Exposure time: 2 h
	LC50 rat: 1,355 mg/l
ethanol:	
Acute oral toxicity	: LD50 Oral rat: 7,060 mg/kg
Acute inhalation toxicity	: LC50 rat: 124.7 mg/l Exposure time: 4 h

Version 1.0

Revision Date 04/14/2015

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

no data available

Germ cell mutagenicity

no data available

Carcinogenicity

no data available

Reproductive toxicity

no data available

butane: 2-butoxyethanol: ethanol:

STOT - single exposure

no data available

STOT - repeated exposure

no data available

Aspiration toxicity

no data available

Further information

Product:

Remarks: no data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

no data available

Persistence and degradability

no data available Bioaccumulative potential

Product:

Version 1.0	Revision Date 04/14/2015	Print Date 10/14/2015
Partition coefficient: n- octanol/water <u>Components:</u> butane :	: Remarks: no data available	
Partition coefficient: n- octanol/water	: Pow: 2.89	
Mobility in soil		
no data available		
Other adverse effects		
no data available <u>Product:</u>		
Regulation	40 CFR Protection of Environme Stratospheric Ozone - CAA Sect Substances	-
Remarks	This product neither contains, no with a Class I or Class II ODS as Clean Air Act Section 602 (40 C + B).	s defined by the U.S.
Additional ecological information	: no data available	

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods	
Waste from residues	 Do not dispose of waste into sewer. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of in accordance with local regulations.
Contaminated packaging	 Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

Transportation Regulation: 49 CFR (USA): ORM-D, CONSUMER COMMODITY

Transportation Regulation: IMDG (Vessel): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Cargo Air): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: IATA (Passenger Air):

Version 1.0

Revision Date 04/14/2015

Print Date 10/14/2015

UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

Transportation Regulation: TDG (Canada): UN1950, AEROSOLS, NON-FLAMMABLE, 2.2, - Limited quantity

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards	: Sudden Release of Pressure Hazard	
SARA 302	: SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.	
SARA 313	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.	
California Prop 65 2,2'-imino	WARNING! This product contains a chemical known to the State of California to cause cancer. diethanol 111-42-2	
The components of this product are reported in the following inventories:		
DSL TI	On TSCA Inventory This product contains the following components that are not on the Canadian DSL nor NDSL.	
NZIOC N	ot in compliance with the inventory ot in compliance with the inventory ot in compliance with the inventory	

IECSC Not in compliance with the inventory

Inventory Acronym and Validity Area Legend:

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIOC (New Zealand), PICCS (Philippines), TSCA (USA)


SECTION 16. OTHER INFORMATION

Version 1.0

Revision Date 04/14/2015

Print Date 10/14/2015

Further information



HMIS III:



0 = not significant, 1 =Slight,

2 = Moderate, 3 = High

4 = Extreme, * = Chronic

OSHA GHS Label Information:



We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes. This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.