SAFETY DATA SHEET

1. Identification

Product identifier Interstate 50

Other means of identification

Product code F1950

Recommended use Floor Finish / Sealer

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Franklin Cleaning Technology Company name

Address One Fuller Way

Great Bend, KS 67530

United States

Telephone **Customer Service** (800) 810-4829

E-mail Not available.

CHEMTREC (800) 424-9300 **Emergency phone number**

> (620) 792-1711 Emergency (800) 424-9300 24 hour Emergency

2. Hazard(s) identification

Not classified. **Physical hazards Health hazards** Not classified. **Environmental hazards** Not classified. Not classified. **OSHA** defined hazards

Label elements

Hazard symbol None. Warning Signal word

Hazard statement May cause mild eye and skin irritation.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Wash hands after handling. Response

Storage Store away from incompatible materials.

Dispose of waste and residues in accordance with local authority requirements. **Disposal**

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
DIETHYLENE GLYCOL MONOETHYL ETHER		111-90-0	5 - < 10
TRIBUTOXYETHYLPHOSPHATE		78-51-3	1 - < 3
Other components below reportable lev	els		90 - 100

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Material name: Interstate 50 SDS US 1/6

Rinse with water. Get medical attention if irritation develops and persists. Eye contact

Ingestion Rinse mouth. Get medical attention if symptoms occur. Direct contact with eyes may cause temporary irritation. Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Treat symptomatically.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting

Move containers from fire area if you can do so without risk.

Specific methods General fire hazards

equipment/instructions

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid prolonged exposure. Observe good industrial hygiene practices.

Conditions for safe storage. including any incompatibilities Store in original tightly closed container. Keep out of the reach of children. Store away from

incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. Workplace Environmental Exposure Level (WEEL) Guides

Components	Туре	Value	
DIETHYLENE GLYCOL MONOETHYL ETHER (CAS 111-90-0)	TWA	140 mg/m3	
		25 nnm	

25 ppm No biological exposure limits noted for the ingredient(s). **Biological limit values**

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Wear safety glasses with side shields (or goggles). Eye/face protection

Material name: Interstate 50 SDS US Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Liquid.
Physical state Liquid.

Form Liquid. Emulsion

Color Off-white.

Odor Matches to Standard

Odor threshold Not available.

pH 9

Melting point/freezing point Not available.

Initial boiling point and boiling 212 °F (100 °C)

range

Flash point 204.8 °F (96.0 °C) estimated

Evaporation rate Not available.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower

(%)

Flammability limit - upper

(%)

Not available.

Not available.

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.01 hPa estimated

Vapor densityNot available.Relative densityNot available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 400 °F (204.44 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

Density 8.62 lbs/gal estimated **Percent volatile** 79.3 % estimated

Pounds per gallon 8.62 lb/gal

Specific gravity 1.04 estimated

VOC (Weight %) 0 % estimated

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Material name: Interstate 50 SDS US

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Expected to be a low ingestion hazard. Ingestion Inhalation Prolonged inhalation may be harmful.

No adverse effects due to skin contact are expected. Skin contact Direct contact with eyes may cause temporary irritation. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Not available. **Acute toxicity**

Product	Species	Test Results	
Interstate 50 (CAS Mixture)		
Acute			
Dermal			
LD50	Rabbit	33687.9414 g/kg estimated	
Oral			
LD50	Mouse	123.1241 g/kg estimated	
	Rat	27269.4727 mg/kg estimated	
Other			
LD50	Mouse	7508.6294 mg/kg estimated	
	Rat	41166.125 mg/kg estimated	

^{*} Estimates for product may be based on additional component data not shown.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation. Serious eye damage/eye Direct contact with eyes may cause temporary irritation.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. Carcinogenicity

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not available. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Material name: Interstate 50 SDS US Product Species Test Results

Interstate 50 (CAS Mixture)

Aquatic

Fish LC50 Fish 510.4688 mg/l, 96 hours estimated

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

DIETHYLENE GLYCOL MONOETHYL ETHER -0.54
TRIBUTOXYETHYLPHOSPHATE 3.75

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations All components are listed or exempted from listing on the U.S. EPA TSCA Inventory List. This

product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

DIETHYLENE GLYCOL MONOETHYL ETHER (CAS Listed

111-90-0)

TRIBUTOXYETHYLPHOSPHATE (CAS 78-51-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

Material name: Interstate 50 SDS US

^{*} Estimates for product may be based on additional component data not shown.

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
DIETHYLENE GLYCOL MONOETHYL ETHER	111-90-0	5 - < 10
ZINK AMMONIA CARBONATE COMPLEX	38714-47-5	< 1

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

DIETHYLENE GLYCOL MONOETHYL ETHER (CAS 111-90-0)

No

TRIBUTOXYETHYLPHOSPHATE (CAS 78-51-3)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Not regulated.

US. New Jersey Worker and Community Right-to-Know Act

DIETHYLENE GLYCOL MONOETHYL ETHER (CAS 111-90-0)

TRIBUTOXYETHYLPHOSPHATE (CAS 78-51-3)

US. Pennsylvania Worker and Community Right-to-Know Law

DIETHYLENE GLYCOL MONOETHYL ETHER (CAS 111-90-0)

TRIBUTOXYETHYLPHOSPHATE (CAS 78-51-3)

US. Rhode Island RTK

DIETHYLENE GLYCOL MONOETHYL ETHER (CAS 111-90-0)

TRIBUTOXYETHYLPHOSPHATE (CAS 78-51-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

 Issue date
 11-20-2014

 Revision date
 05-13-2015

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Physical & Chemical Properties: Multiple Properties

Toxicological Information: Toxicological Data

Transport Information: Agency Name, Packaging Type, and Transport Mode Selection

Material name: Interstate 50 SDS US