FRANKLIN CLANNG TECNOLOGY

SAFETY DATA SHEET

1. Identification

Product identifier Once Over

Other means of identification

Product code F200022, F200026, F200038

Recommended use Floor Stripper **Recommended restrictions** None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Franklin Cleaning Technology

Address One Fuller Way

Great Bend, KS 67530

United States

Telephone Customer Service (800) 810-4829

E-mail Not available.

Emergency phone number CHEMTREC (800) 424-9300

Emergency (620) 792-1711 24 hour Emergency (800) 424-9300

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 4Health hazardsAcute toxicity, oralCategory 4

Acute toxicity, dermal Category 4
Serious eye damage/eye irritation Category 1

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Hazardous to the aquatic environment, acute Category 3

hazard

Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Combustible liquid. Harmful if swallowed. Harmful in contact with skin. Causes serious eye

damage. May cause respiratory irritation. Harmful to aquatic life. Harmful to aquatic life with long

Category 3

lasting effects.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Avoid breathing mist or

vapor. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective

 ${\it gloves/protective\ clothing.}\ We ar\ protective\ {\it gloves/eye}\ protection/face\ protection.$

Response If swallowed: Call a poison center/doctor if you feel unwell. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see this label). Rinse mouth. Take off contaminated clothing and wash before reuse. In case of fire: Use

appropriate media to extinguish.

Storage Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place.

Keep cool. Store locked up.

Material name: Once Over SDS US

822 Version #: 02 Revision date: 09-22-2014 Issue date: 06-05-2014

Disposal

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations. None known.

Supplemental information

5.4% of the mixture consists of component(s) of unknown acute oral toxicity. 9.98% of the mixture consists of component(s) of unknown acute dermal toxicity. 29.4% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 29.4% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
BUTOXYETHANOL		111-76-2	10 - < 20
2-aminoethanol		141-43-5	3 - < 5
ETHYLENE GLYCOL PHENYL ETHER		122-99-6	3 - < 5
Other components below reportable lev	vels		70 - < 80

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Rinse skin with water/shower. Get medical advice/attention if you feel unwell. Get medical attention Skin contact

if irritation develops and persists. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention immediately.

Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Ingestion

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Alcohol resistant foam. Water fog. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

The product is combustible, and heating may generate vapors which may form explosive vapor/air mixtures. During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Combustible liquid.

6. Accidental release measures

Personal precautions. protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Once Over SDS US

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Keep away from open flames, hot surfaces and sources of ignition. Do not get in eyes, on skin, or on clothing. Avoid breathing mist or vapor. Avoid prolonged exposure. Do not taste or swallow. When using, do not eat, drink or smoke. Provide adequate ventilation. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Wash contaminated clothing before reuse. Avoid release to the environment. Do not empty into drains.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Store in a cool, dry place out of direct sunlight. Store in original tightly closed container. Store in a well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	Value	
2-aminoethanol (CAS 141-43-5)	PEL	6 mg/m3	
•		3 ppm	
BUTOXYETHANOL (CAS 111-76-2)	PEL	240 mg/m3	
,		50 ppm	
US. ACGIH Threshold Limit Value	s		
Components	Туре	Value	
2-aminoethanol (CAS 141-43-5)	STEL	6 ppm	
,	TWA	3 ppm	
BUTOXYETHANOL (CAS 111-76-2)	TWA	20 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
2-aminoethanol (CAS 141-43-5)	STEL	15 mg/m3	
		6 ppm	
	TWA	8 mg/m3	
		3 ppm	
BUTOXYETHANOL (CAS 111-76-2)	TWA	24 mg/m3	
·		5 ppm	

Material name: Once Over SDS US

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time
BUTOXYETHANOL (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA),	Creatinine in urine	*
		with hydrolysis		

^{* -} For sampling details, please see the source document.

Exposure guidelines

US - California OELs: Skin designation

BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US - Minnesota Haz Subs: Skin designation applies

BUTOXYETHANOL (CAS 111-76-2) Skin designation applies.

US - Tennesse OELs: Skin designation

BUTOXYETHANOL (CAS 111-76-2) Can be absorbed through the skin.

US NIOSH Pocket Guide to Chemical Hazards: Skin designation

BUTOXYETHANOL (CAS 111-76-2)

Can be absorbed through the skin.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

BUTOXYETHANOL (CAS 111-76-2)

Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles) and a face shield.

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Chemical respirator with organic vapor

cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Liquid.
Form Liquid.
Color Colorless
Odor Solvent.
Odor threshold Not available.
pH 12.3 - 12.4

Melting point/freezing point -102.64 °F (-74.8 °C) estimated Initial boiling point and boiling 335.12 °F (168.4 °C) estimated

range

Flash point 143.0 °F (61.7 °C) estimated

Evaporation rate Not available.
Flammability (solid, gas) Not available.
Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Material name: Once Over SDS US

822 Version #: 02 Revision date: 09-22-2014 Issue date: 06-05-2014

Flammability limit - upper

(%)

Not available.

Explosive limit - lower (%) Not available. Explosive limit - upper (%) Not available.

Vapor pressure 0.22 hPa estimated

Not available. Vapor density Not available. Relative density

Solubility(ies)

Solubility (water) Not available. **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature 460.4 °F (238 °C) estimated

Decomposition temperature Not available. **Viscosity** Not available.

Other information

8.27 lbs/gal estimated Density Combustible IIIA estimated Flammability class

93.02 % estimated Percent volatile

Specific gravity 1.01 - 1.02 VOC (Weight %) 24 % estimated

10. Stability and reactivity

Reacts violently with strong acids. This product may react with oxidizing agents. Reactivity

Material is stable under normal conditions. **Chemical stability** Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Do not mix with other chemicals. Contact with incompatible materials.

Incompatible materials Acids. Strong oxidizing agents. Oxidizing agents. **Hazardous decomposition**

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Ingestion Harmful if swallowed.

Prolonged inhalation may be harmful. May cause irritation to the respiratory system. Inhalation

Skin contact Harmful in contact with skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Severe eve irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation.

Information on toxicological effects

Acute toxicity In high concentrations, vapors are anesthetic and may cause headache, fatigue, dizziness and

central nervous system effects. Harmful in contact with skin. Harmful if swallowed. May cause

respiratory irritation.

Material name: Once Over SDS US Product Species Test Results

Once Over (CAS Mixture)

Acute

Dermal

LD50 Rabbit 2228.261 mg/kg estimated

Inhalation

LC50 Mouse 4375 ppm, 7 Hours estimated

Rat 2812.5 ppm, 4 Hours estimated

Oral

LD50 Mouse 7.5 g/kg estimated

Rat 3134.2554 mg/kg estimated

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutes 250.0000
Erythema value 0.0000
Oedema value 0.0000

Serious eye damage/eye

irritation

Causes serious eye damage.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicityNo data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

IARC Monographs. Overall Evaluation of Carcinogenicity

BUTOXYETHANOL (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effects Prolonged inhalation may be harmful. May be harmful if absorbed through skin.

2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and

prolonged. These effects have not been observed in humans.

Prolonged or repeated exposure may cause liver and kidney damage. These effects have not

been observed in humans.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Persistence and degradability
No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2-aminoethanol -1.31
BUTOXYETHANOL 0.83
ETHYLENE GLYCOL PHENYL ETHER 1.16

Mobility in soil No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

Material name: Once Over

^{*} Estimates for product may be based on additional component data not shown.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code This substance/mixture is not intended to be transported in bulk.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are listed or exempted from listing on the U.S. EPA

TSCA Inventory List.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

BUTOXYETHANOL (CAS 111-76-2)

Listed.

ETHYLENE GLYCOL PHENYL ETHER (CAS 122-99-6) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
BUTOXYETHANOL	111-76-2	10 - < 20	_
ETHYLENE GLYCOL PHENYL ETHER	122-99-6	3 - < 5	

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

ETHYLENE GLYCOL PHENYL ETHER (CAS 122-99-6)

Material name: Once Over sps us

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

2-aminoethanol (CAS 141-43-5) BUTOXYETHANOL (CAS 111-76-2)

US. New Jersey Worker and Community Right-to-Know Act

2-aminoethanol (CAS 141-43-5) BUTOXYETHANOL (CAS 111-76-2)

ETHYLENE GLYCOL PHENYL ETHER (CAS 122-99-6)

US. Pennsylvania Worker and Community Right-to-Know Law

2-aminoethanol (CAS 141-43-5) BUTOXYETHANOL (CAS 111-76-2)

ETHYLENE GLYCOL PHENYL ETHER (CAS 122-99-6)

US. Rhode Island RTK

BUTOXYETHANOL (CAS 111-76-2)

ETHYLENE GLYCOL PHENYL ETHER (CAS 122-99-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

16. Other information, including date of preparation or last revision

 Issue date
 06-05-2014

 Revision date
 09-22-2014

Version # 02

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Revision Information Product and Company Identification: Alternate Trade Names

Toxicological Information: Toxicological Data Regulatory information: US federal regulations

Material name: Once Over sps us