

Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

SECTION 1. IDENTIFICATION

Product name : GOJO® Antibacterial Plum Foam Handwash

Manufacturer or supplier's details

Company name of supplier : GOJO Industries, Inc.

Address : One GOJO Plaza, Suite 500

Akron OH 44311

Telephone : 1 (330) 255-6000

Emergency telephone : 1-800-424-9300 CHEMTREC

Recommended use of the chemical and restrictions on use

Recommended use : Antibacterial Soap

Restrictions on use : This is a personal care or cosmetic product that is safe for

consumers and other users under normal and reasonably foreseeable use. Cosmetics and consumer products, specifically defined by regulations around the world, are exempt from the requirement of an SDS for the consumer. While this material is not considered hazardous, this SDS contains valuable information critical to the safe handling and proper use of the product for industrial workplace conditions as well as unusual and unintended exposures such as large spills. This SDS should be retained and available for employees and other users of this product. For specific

provided on the package or instruction sheet.

intended-use guidance, please refer to the information

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids : Category 3

Serious eye damage : Category 1

GHS Label element

Hazard pictograms :





Signal Word : Danger

Hazard Statements : H226 Flammable liquid and vapor.

H318 Causes serious eye damage.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Precautionary Statements : **Prevention:**

P210 Keep away from heat/sparks/open flames/hot surfaces.

No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof electrical/ ventilating/ lighting/

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge. P280 Wear protective gloves/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately

all contaminated clothing. Rinse skin with water/shower.

P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON

CENTER or doctor/ physician.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Disposal:

P501 Dispose of contents/ container to an approved waste

disposal plant.

Other hazards

Vapors may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Ethanol	64-17-5	>= 10 - < 20
Dodecanoic acid	143-07-7	>= 5 - < 10
Propylene glycol	57-55-6	>= 5 - < 10
Ethanolamine	141-43-5	>= 1 - < 5
Imidazolium compounds, 1-[2- (carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5- dihydro-2-norcoco alkyl, hydroxides, sodium salts	68650-39-5	>=1 -<5

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

advice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : Wash with water and soap as a precaution.

Get medical attention if symptoms occur.



Version **Revision Date:** MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

In case of eye contact : In case of contact, immediately flush eyes with plenty of water

for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention immediately.

If swallowed : If swallowed, DO NOT induce vomiting.

> Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: Causes serious eye damage.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment

when the potential for exposure exists.

: Treat symptomatically and supportively. Notes to physician

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

> Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during fire

fighting

: Do not use a solid water stream as it may scatter and spread

fire.

Flash back possible over considerable distance. Vapors may form explosive mixtures with air.

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

: Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : Remove all sources of ignition.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

protective equipment and emergency procedures

Use personal protective equipment.

Follow safe handling advice and personal protective

equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so.

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

: Non-sparking tools should be used.

Soak up with inert absorbent material.

Suppress (knock down) gases/vapors/mists with a water spray

jet.

For large spills, provide diking or other appropriate

containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate

container.

Clean up remaining materials from spill with suitable

absorbent.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items

employed in the cleanup of releases. You will need to

determine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use with local exhaust ventilation.

Use only in an area equipped with explosion proof exhaust

ventilation.

Advice on safe handling : Avoid inhalation of vapor or mist.

Do not swallow. Do not get in eyes.

Avoid prolonged or repeated contact with skin.

Handle in accordance with good industrial hygiene and safety

practice.

Non-sparking tools should be used. Keep container tightly closed.

Keep away from heat and sources of ignition.

Take precautionary measures against static discharges.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Keep tightly closed.

Keep in a cool, well-ventilated place.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Store in accordance with the particular national regulations.

Keep away from heat and sources of ignition.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents
Organic peroxides
Flammable solids
Pyrophoric liquids
Pyrophoric solids

Self-heating substances and mixtures

Substances and mixtures which in contact with water emit

flammable gases

Explosives Gases

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Ethanol	64-17-5	TWA	1,000 ppm 1,900 mg/m3	NIOSH REL
		TWA	1,000 ppm 1,900 mg/m3	OSHA Z-1
		STEL	1,000 ppm	ACGIH
Propylene glycol	57-55-6	TWA	10 mg/m3	US WEEL
Ethanolamine	141-43-5	TWA	3 ppm	ACGIH
		STEL	6 ppm	ACGIH
		TWA	3 ppm 8 mg/m3	NIOSH REL
		ST	6 ppm 15 mg/m3	NIOSH REL
		TWA	3 ppm 6 mg/m3	OSHA Z-1

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Dodecanoic acid	143-07-7
Imidazolium compounds, 1-[2- (carboxymethoxy)ethyl]-1- (carboxymethyl)-4,5-dihydro-2-	68650-39-5
norcoco alkyl, hydroxides, sodium salts	

Engineering measures : Minimize workplace exposure concentrations.

Use only in an area equipped with explosion proof

exhaust ventilation.

Use with local exhaust ventilation.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and

use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any

hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other

circumstance where air purifying respirators may not provide

adequate protection.

Hand protection

Material : Impervious gloves

Material : Flame retardant gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Chemical resistant goggles must be worn. If splashes are likely to occur, wear:

Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Wear the following personal protective equipment:

Flame retardant antistatic protective clothing.

Skin contact must be avoided by using impervious protective

clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers are

located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Color : clear, purple

Odor : citrus

SAFETY DATA SHEET



GOJO® Antibacterial Plum Foam Handwash

Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Odor Threshold : No data available

pH : 7.8 - 9.7

Melting point/freezing point : No data available

Initial boiling point and boiling

range

: 97.00 °C

Flash point : 56.00 °C

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : No data available

Relative vapor density : No data available

Density : 1.00 g/cm3

Solubility(ies)

Water solubility : soluble

Partition coefficient: n-

octanol/water

: Not applicable

Autoignition temperature : No data available

Decomposition temperature : The substance or mixture is not classified self-reactive.

Viscosity

Viscosity, kinematic : 10 - 20 mm2/s (20 °C)

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

: Flammable liquid and vapor.

Vapors may form explosive mixture with air.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

: No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 40 mg/l

Exposure time: 4 h
Test atmosphere: vapor
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

Ethanol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): 124.7 mg/l

Exposure time: 4 h Test atmosphere: vapor

Dodecanoic acid:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 0.162 mg/l

Exposure time: 4 h Test atmosphere: vapor

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on data from similar materials

Propylene glycol:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rabbit): > 159 mg/l, > 51091 ppm

Exposure time: 4 h



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Ethanolamine:

Acute oral toxicity : LD50 (Rat): 1,515 mg/kg

Acute inhalation toxicity : Acute toxicity estimate: 11 mg/l

Test atmosphere: vapor Method: Expert judgment

Remarks: Based on harmonised classification in EU regulation

1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit): 1,025 mg/kg

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Acute oral toxicity : LD50 (Rat, male): > 5,000 mg/kg

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 402

Remarks: Based on data from similar materials

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: No skin irritation

Ingredients:

Ethanol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Dodecanoic acid: Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Propylene glycol:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Ethanolamine: Species: Rabbit

Result: Corrosive after 3 minutes to 1 hour of exposure



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Remarks: Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Ingredients:

Ethanol:

Species: Rabbit

Result: Irritation to eyes, reversing within 21 days

Method: OECD Test Guideline 405

Dodecanoic acid:

Species: Rabbit

Result: Irreversible effects on the eye Method: OECD Test Guideline 405

Propylene glycol:

Species: Rabbit

Result: No eye irritation

Method: OECD Test Guideline 405

Ethanolamine:

Species: Rabbit

Result: Irreversible effects on the eye

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Species: Rabbit

Result: Irreversible effects on the eye Method: OECD Test Guideline 405

Remarks: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization: Not classified based on available information.

Respiratory sensitization: Not classified based on available information.

Product:

Assessment: Does not cause skin sensitization.

<u>Ingredients:</u>

Ethanol:

Test Type: Local lymph node assay (LLNA)

Routes of exposure: Skin contact

Species: Mouse Result: negative

Dodecanoic acid:

Test Type: Maximization Test (GPMT)



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Propylene glycol:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Ethanolamine:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact

Species: Guinea pig Result: negative

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Test Type: Maximization Test (GPMT) Routes of exposure: Skin contact

Species: Guinea pig

Method: OECD Test Guideline 406

Result: negative

Remarks: Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Ethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)

Species: Mouse

Application Route: Ingestion

Result: negative

Dodecanoic acid:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Propylene glycol:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Ethanolamine:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Method: OECD Test Guideline 476

Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo

cytogenetic assay)
Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 474

Result: negative

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Method: OECD Test Guideline 473

Result: negative

Remarks: Based on data from similar materials

: Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Remarks: Based on data from similar materials

: Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: Based on data from similar materials

Carcinogenicity

Not classified based on available information.

Ingredients:

Propylene glycol:

Species: Rat

Application Route: Ingestion Exposure time: 2 Years Result: negative

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Ethanol:

Effects on fertility : Test Type: Two-generation reproduction toxicity study



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Species: Mouse

Application Route: Ingestion Method: OECD Test Guideline 416

Result: negative

Dodecanoic acid:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

Remarks: Based on data from similar materials

Propylene glycol:

Effects on fertility : Species: Mouse

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Mouse

Application Route: Ingestion

Result: negative

Ethanolamine:

Effects on fertility : Test Type: Two-generation reproduction toxicity study

Species: Rat

Application Route: Ingestion

Result: negative

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 414

Result: negative

STOT-single exposure

Not classified based on available information.

Ingredients:

Ethanolamine:

Assessment: May cause respiratory irritation.

STOT-repeated exposure

Not classified based on available information.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Ingredients:

Ethanolamine:

Routes of exposure: inhalation (dust/mist/fume)

Assessment: No significant health effects observed in animals at concentrations of 0.2 mg/l/6h/d

or less.

Repeated dose toxicity

Ingredients:

Ethanol: Species: Rat

NOAEL: 2,400 mg/kg

Application Route: Ingestion

Exposure time: 2 y

Dodecanoic acid:

Species: Rat

NOAEL: 10,000 mg/kg Application Route: Ingestion

Exposure time: 18 w

Propylene glycol:

Species: Rat

NOAEL: 1,700 mg/kg Application Route: Ingestion

Exposure time: 2 y

Ethanolamine:

Species: Rat

NOAEL: 150 mg/m3

Application Route: inhalation (dust/mist/fume)

Exposure time: 28 d

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Species: Rat, female NOAEL: 250 mg/kg LOAEL: 500 mg/kg

Application Route: Ingestion

Exposure time: 28 d

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Ethanol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 1,000 mg/l

Exposure time: 96 h



Version **Revision Date:** MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h

: EC50 (Chlorella vulgaris (Fresh water algae)): 275 mg/l Toxicity to algae

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 9.6 mg/l

Exposure time: 9 d

Toxicity to bacteria : EC50 (Photobacterium phosphoreum): 32.1 mg/l

Exposure time: 0.25 h

Dodecanoic acid:

Toxicity to fish : LC50 (Oryzias latipes (Japanese medaka)): 5 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 3.6 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

NOEC (Selenastrum capricornutum (green algae)): > 7.6 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility.

Toxicity to fish (Chronic

toxicity)

: NOEC (Danio rerio (zebra fish)): 2 mg/l

Exposure time: 28 d

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.47 mg/l Exposure time: 21 d

Method: OECD Test Guideline 211

Toxicity to bacteria : EC10 (Pseudomonas putida): > 1,000 mg/l

Exposure time: 30 min

Method: OECD Test Guideline 209

Propylene glycol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 40,613 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Ceriodaphnia dubia (water flea)): 18,340 mg/l

Exposure time: 48 h

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 19,000 mg/l

Exposure time: 48 h



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: Chronic Toxicity Value: 2,500 mg/l

Exposure time: 30 d

Toxicity to daphnia and other aquatic invertebrates

aquatic invertebra (Chronic toxicity)

: NOEC (Ceriodaphnia dubia (water flea)): 29,000 mg/l

Exposure time: 7 d

Toxicity to bacteria : NOEC (Pseudomonas putida): > 20,000 mg/l

Exposure time: 18 h

Ethanolamine:

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 349 mg/l

Exposure time: 96 h

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia magna (Water flea)): 65 mg/l

Exposure time: 48 h

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 2.8 mg/l

Exposure time: 72 h

NOEC (Scenedesmus capricornutum (fresh water algae)): 1

mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

: NOEC (Oryzias latipes (Orange-red killifish)): 1.24 mg/l

Exposure time: 41 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEC (Daphnia magna (Water flea)): 0.85 mg/l

Exposure time: 21 d

Toxicity to bacteria : EC50 (Pseudomonas putida): 110 mg/l

Exposure time: 17 h

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4.2 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 17.9 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 3.2

mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3. Remarks: Based on data from similar materials

ErC50 (Pseudokirchneriella subcapitata (green algae)): 10



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

mg/l

Exposure time: 72 h

Method: Directive 67/548/EEC, Annex V, C.3. Remarks: Based on data from similar materials

Persistence and degradability

Product:

Biodegradability : Result: Biodegradable

Ingredients:

Ethanol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 84 % Exposure time: 20 d

Dodecanoic acid:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 86 % Exposure time: 30 d

Method: OECD Test Guideline 301D

Propylene glycol:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 98.3 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Ethanolamine:

Biodegradability : Result: Readily biodegradable.

Biodegradation: > 90 % Exposure time: 21 d

Imidazolium compounds, 1-[2-(carboxymethoxy)ethyl]-1-(carboxymethyl)-4,5-dihydro-2-norcoco alkyl, hydroxides, sodium salts:

Biodegradability : Result: Readily biodegradable.

Biodegradation: 79 % Exposure time: 28 d

Method: OECD Test Guideline 301F

Remarks: Based on data from similar materials

Bioaccumulative potential

Ingredients:

Ethanol:

Partition coefficient: n-

: log Pow: -0.35

octanol/water

Dodecanoic acid:

Bioaccumulation : Species: Fish

Bioconcentration factor (BCF): 234 - 288

Remarks: Based on data from similar materials

SAFETY DATA SHEET



GOJO® Antibacterial Plum Foam Handwash

Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

Partition coefficient: n-

octanol/water

: Pow: 4.6

Propylene glycol:

Partition coefficient: n-

octanol/water

: log Pow: -1.07

Ethanolamine:

Partition coefficient: n-

octanol/water

: log Pow: -1.91

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDER ATIONS

Disposal methods

Waste from residues Dispose of in accordance with local regulations

Contaminated packaging Dispose of as unused product.

Empty containers should be taken to an approved waste handling site for recycling or

disposal.

Do not burn, or use a cutting torch on, the empty

drum

SECTION 14. TRANSPORT INFORMATION

This Section not required under 29 CFR 1910.1200

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Fire Hazard

Acute Health Hazard

SARA 302 : No chemicals in this material are subject to the reporting

requirements of SARA Title III, Section 302.



Version Revision Date: MSDS Number:

WM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

US State Regulations

Pennsylvania Right To Know

Water	7732-18-5	70 - 90 %
Ethanol	64-17-5	10 - 20 %
Propylene glycol	57-55-6	5 - 10 %
Dodecanoic acid	143-07-7	5 - 10 %
Ethanolamine	141-43-5	1 - 5 %
Propan-2-ol	67-63-0	0.1 - 1 %

New Jersey Right To Know

Water	7732-18-5	70 - 90 %
Ethanol	64-17-5	10 - 20 %
Propylene glycol	57-55-6	5 - 10 %
Dodecanoic acid	143-07-7	5 - 10 %
Ethanolamine	141-43-5	1 - 5 %

California Prop 65 This product does not contain any chemicals known to the

State of California to cause cancer, birth, or any other

reproductive defects.

The ingredients of this product are reported in the following inventories:

AICS : All ingredients listed or exempt.

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION


Further information



Version Revision Date: MSDS Number: WM 06/16/2015 31854-00003

VM 06/16/2015 31854-00003 Date of first issue: 11/24/2014

NFPA:



Special hazard.

HMIS III:

HEALTH	 3
FLAMMABILITY	2
PHYSICAL HAZARD	lo l

0 = not significant, 1 = Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1 Lim-

its for Air Contaminants

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA Z-1 / TWA : 8-hour time weighted average

US WEEL / TWA : 8-hr TWA

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 06/16/2015

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information pro-vided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, un-less specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8



<u>Document Number: SDS100</u> Revision: 00 Date of prepared: 26 May 2015

Section I – Product and Company Identification			
Information of Product			
Product Identity (used on the label)	Cylindrical Alkaline Battery – LR20, LR14, LR6, LR03		
Information of Manufacturer			
Manufacturer's Name		Emergency Telephone Number	
GPI International Ltd.		Within USA & Canada call: +1-800-424-9300	
		Outside USA and Canada call: +1-703-527-3887	
Address (Number, Street, City State, a	and ZIP Code)	Telephone Number for Information	
8/F GP Building, 30 Kwai Wing Road, Kwai Chung, N.T.,		+852-24843333	
Hong Kong			
		Date of prepared and revised	
		26 th May 2015	
Recommended use of chemicals:		1	

N.A.

Section II - Hazards Identification


Hazards identifications

General advice: The common known rules for handling of chemicals should be obeyed. These chemicals are contained in a sealed steel can. For consumer use, adequate hazard warnings are printed on both the package and the battery. Potential for exposure should not exist unless the battery leaks, is exposed to high temperatures or is mechanically or electrically abused. Concentrated potassium hydroxide contained is caustic. Anticipated potential leakage of potassium hydroxide is 2-20 ml, depending on battery size. Do not eat and drink batteries. Keep batteries away from small children.

Physical-Chemical Hazards: This preparation is not classified as dangerous according to the criteria of directive 99/45/EEC.

Hazards to man: If battery leaking, exposure to caustic ingredients may occur. Therefore, may cause sensitization by skin contract.

Hazards to environment: N.A.





<u>Document Number: SDS100</u> Revision: 00 Date of prepared: 26 May 2015

Section III – Composition/Information on Ingredients

Chemical Nature: Alkaline zinc-manganese dioxide batteries

Ingredient CAS No.	CAS No.	Approximate %/wt			
	LR03	LR6	LR14	LR20	
Manganese Dioxide (MnO2)	1313-13-9	40.9	42.6	40.6	41.8
Zinc (Zn)	7440-66-6	14.8	16.1	16.0	17.4
Water (H2O)	7732-18-5	11.7	12.2	11.0	11.1
Potassium Hydroxide (KOH)	1310-58-3	4.8	5.2	7.0	7.0
Graphite	7782-42-5	1.7	3.0	3.2	3.4
Brass	12597-71-6	3.0	2.4	1.2	0.8
Steel	7439-89-6	20.4	15.7	18.6	16.3
Ni-plating	7440-02-0	0.3	0.3	0.2	0.2
Nylon-66	None	1.5	1.6	1.6	1.4
Fiber	None	0.9	0.9	0.6	0.6
Mercury (Hg)	7439-97-6	<0.0001	<0.0001	<0.0001	<0.0001
Lead (Pb)	7439-92-1	<0.0030	<0.0030	<0.0030	<0.0030
Cadmium (Cd)	7440-43-9	<0.0003	<0.0003	<0.0003	<0.0003
Arsenic (As)	7440-38-2	<0.0001	<0.0001	<0.0001	<0.0001


Section IV – First-aid Measures

Inhalation: In case of excessive inhalation due to leaking batteries remove to fresh air. Obtain medical advice.

Skin Contact: If exposed to a leaking battery, remove contaminated clothing. Wash exposed areas with plenty of water and soap. If irritation occurs, consult a physician.

Eye contact: If a battery is leaking and materials contact eyes, flush immediately with running water for at least 15 minutes. Consult an ophthalmologist at once.

Ingestion: Not anticipated due to size of batteries. Choking may occur with the smaller size batteries. If exposed to a leaking battery, rinse mouth and surrounding areas with running water for at least 15 minutes. Give plenty of water to drink. Do not induce vomiting. Obtain medical advice.





Document Number: SDS100 Revision: 00 Date of prepared: 26 May 2015

Section V – Fire-fighting Measures

Suitable extinguishing media: Carbon dioxide (CO2), foam, dry chemical powder.

Extinguishing media not to be used: Never use a direct water jet.

Exposure hazards from combustion products: In case of fire, carbon dioxide, carbon monoxide and other toxic organic substances will be generated. Do not inhale fumes and smoke.

Personal protective equipments: Wear full protective clothing. Use self-contained breathing apparatus.

Section VI - Accidental Release Measures

Personal precautions: Notify safety personnel of large spills. Caustic potassium hydroxide may be released from leaking or ruptured batteries. Avoid eye or skin contact and inhalation of vapours. Increase the ventilation. Wear protective clothing. Keep unprotected persons away.

Environmental precautions: Avoid discharge and penetration into sewerage systems, waterways, pits, and cellars. **Methods for cleaning up:** Collect spilled material with an insert standard absorbent like sand or silica. Care for well-ventilated conditions. Recycle or dispose of the materials in an appropriate way.

Section VII - Handling and Storage

General handling:

Obey the common known rules and precautions for handling with chemicals. Avoid mechanical and electrical abuse. Do not short battery or install incorrectly. Batteries may explode, pyrolize or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries according to equipment instructions. Do not mix battery systems, such as alkaline and zinc- carbon. Replace all batteries in equipment at the same time. Do not carry batteries loose in pocket or bag. Do not remove battery labels.


Storage:

Store product in well-filled, appropriate coated and tightly closed containers avoiding influence of oxygen/air, light and humidity. Storage at room temperature.

Section VIII – Exposure Controls/Personal Protection

Exposition/Technical measures: Atmospheric vapour concentrations must be minimized by adequate ventilation. **Protection of hands, eyes and skin:** None required under normal use conditions. When handling leaking batteries, use neoprene, rubber or nitrile gloves and wear safety glasses to protect hands, eyes and skin.

General safety and hygiene measures: Use only as directed.





Document Number: SDS100 Revision: 00 Date of prepared: 26 May 2015

Section IX – Physical and Chemical Properties

Physical state: Stainless steel top battery Colour: Contents dark and gray in colour

Odour: N.A.

Melting point: N.A. Boiling point: N.A. Flash point: N.A.

Explosion limit: Not available

Ignition temperature: Not available Vapour pressure: Not available

Specific gravity: N.A. Solubility in water: N.A.

Solubility in other solvents: N.A.

PH value: Not available

Partition coefficient: Not available

Viscosity: Not available

Section X – Stability and Reactivity

Thermal decomposition: Batteries may burst and release hazardous decomposition products when exposed to fire. Substances to avoid: Strong oxidation agents.

Hazardous reactions: Contents incompatible with strong oxidizing agents.

Hazardous decomposition products: Thermal degradation may produce hazardous fumes of zinc and manganese;

hydrogen gas; caustic vapors of potassium hydroxide and other toxic by-products.

Section XI – Toxicological Information

Toxicity information is available on the battery ingredients noted in Section III, but in general, N.A. to intact batteries Chronic health effects: N.A.


Section XII - Ecological Information

Not available.

Section XIII – Disposal Considerations

Product: Dispose in accordance with appropriate regulations. If in doubt, contact your local government office concerned for information. Do not incinerate, since batteries may explode at excessive temperatures.

Remark: "N.A." is indicated if not applicable.



Manufacturer reserves the right to alter or amend the design, model and specification without prior notice.



Document Number: SDS100 Revision: 00 Date of prepared: 26 May 2015

Section XIV – Transport Information

Road (ADR/RID): Not regulated

Air (ICAO/IATA):

IATA DGR (55th): Special Provision A123: "Examples of such batteries are: alkali-manganese, zinc-carbon, nickel-metal hydride and nickel-cadmium batteries. Any electrical battery ... having the potential of a dangerous evolution of heat must be prepared for transport as to prevent (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals...) is forbidden from transport; and (b) accidental activation. The words "Not Restricted" and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued."

Sea (IMDG):

IMDG CODE:Special Provision 304 which says: "Batteries, dry, containing corrosive electrolyte which will not flow out of the battery if the battery case is cracked are not subject to the provisions of this Code provided the batteries are securely packed and protected against short-circuits. Examples of such batteries are: alkaline-manganese, zinc-carbon, nickel metal hydride and nickel-cadmium batteries"

These batteries are not regulated by international agencies as hazardous materials or dangerous goods when shipped. A shipping name of "Alkaline Batteries – Non-hazardous" may be used on all domestic and international bills of lading.

In general, all batteries in all forms of transportation (ground, air, or ocean) must be packaged in a safe and responsible manner. Regulatory concerns from all agencies for safe packaging require that batteries be packaged in a manner that prevents short circuits and be contained in "strong outer packaging" that prevents spillage of contents. All original packaging for GP alkaline batteries has been designed to be compliant with these regulatory concerns.

Section XV – Regulatory Information

Symbol: N.A.


EC labeling: None

Risk phrases: None

Safety phrases: None

Labeling is not required because cylindrical alkaline batteries are classified as "articles "under the Dangerous

Preparations Directive and as such are exempt from the requirements of the Directive.





Document Number: SDS100 Revision: 00 Date of prepared: 26 May 2015

Section XVI – Other Information

The information on this Safety Date Sheet (SDS) was obtained form current and reputable sources. However, the data is provided without any warranty; expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to assume liability on loss, injury, damage, or expense resulting from improper use of this product. Any previous MSDS of this product mentioned above are hereby replaced with this new document. We urge you to make this information available as appropriate in your organization and to any others with whom you arrange to handle this product.

