

Revision Number: 002.4 Issue date: 08/04/2016

1. PRODUCT AND COMPANY IDENTIFICATION

IDH number:

Product name: Loctite Professional Performance

Spray Adhesive

Product type: Adhesive Restriction of Use: None identified

Company address: Henkel Corporation One Henkel Way

Rocky Hill, Connecticut 06067

Region: **United States**

Contact information:

Telephone: (860) 571-5100

MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC

1629134

1-800-424-9300 (toll free) or 1-703-527-3887

Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CONTENTS UNDER PRESSURE.

> FLAMMABLE AEROSOL. CAUSES SKIN IRRITATION.

CAUSES SERIOUS EYE IRRITATION.

MAY CAUSE DROWSINESS OR DIZZINESS.

| HAZARD CLASS | HAZARD CATEGORY |
|--|-----------------|
| FLAMMABLE AEROSOL. | 2 |
| SKIN IRRITATION | 2 |
| EYE IRRITATION | 2A |
| SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE | 3 |





Precautionary Statements

Prevention: Keep away from heat, sparks, open flames, hot surfaces - no smoking. Do not spray on an

open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing mist or spray. Wash affected area thoroughly after handling. Use only outdoors or in a well-

ventilated area. Wear protective gloves, eye protection, and face protection.

IF ON SKIN: Wash with plenty of water. IF INHALED: Remove victim to fresh air and keep at Response:

rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical attention. If eye

irritation persists: Get medical attention. Take off contaminated clothing.

Storage: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Disposal: Dispose of contents and/or container according to Federal, State/Provincial and local

governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s) | CAS Number | Percentage* | |
|---|------------|-------------|--|
| Acetone | 67-64-1 | 10 - 30 | |
| Methyl acetate | 79-20-9 | 10 - 30 | |
| Solvent naphtha (petroleum), light aliphatic, low benzene content | 64742-89-8 | 5 - 10 | |
| Cyclohexane | 110-82-7 | 30 - 60 | |
| Propane | 74-98-6 | 10 - 30 | |

^{*} Exact percentage is a trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation: If inhaled, immediately remove the affected person to fresh air. If symptoms

develop and persist, get medical attention.

Skin contact: Wash affected area immediately with soap and water. If symptoms develop

and persist, get medical attention. Remove contaminated clothes.

Eye contact: In case of contact with the eyes, rinse immediately with plenty of water for 15

minutes, and seek immediate medical attention.

Ingestion: Get immediate medical attention. Do not induce vomiting.

Symptoms: See Section 11.

Notes to physician: This material is an aspiration hazard. Potential danger from aspiration must

be weighed against possible oral toxicity when deciding whether to induce

vomiting.

5. FIRE FIGHTING MEASURES

Extinguishing media: Water spray (fog), foam, dry chemical or carbon dioxide.

Special firefighting procedures: Wear full protective clothing. Wear self contained breathing apparatus.

Unusual fire or explosion hazards: May liberate large quantities of dense, foul-smelling smoke which may contain

unidentified toxic gasses. Contents under pressure. Do not puncture or incinerate pressurized containers. Exposure to temperatures above 49°C

(120°F) may cause container to burst.

Hazardous combustion products: Upon decomposition, this product emits carbon monoxide, carbon dioxide

and/or low molecular weight hydrocarbons. Oxides of nitrogen.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions: Prevent further leakage or spillage if safe to do so. Wear appropriate

protective equipment and clothing during clean-up. Do not allow product to

enter sewer or waterways.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for

disposal. Dispose of according to Federal, State and local governmental

regulations.

7. HANDLING AND STORAGE

Handling: Avoid contact with eyes, skin and clothing. Wash thoroughly after handling.

Avoid breathing vapors or mists of this product. Do not take internally.

Storage: For safe storage, store at or below 48.8 °C (119.8 °F)

Keep container tightly closed and in a cool, well-ventilated place away from

incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s) | ACGIH TLV | OSHA PEL | AIHA WEEL | OTHER |
|---|--|--------------------------------|-----------|-------|
| Acetone | 250 ppm TWA 500 ppm STEL | 1,000 ppm (2,400 mg/m3) PEL | None | None |
| Methyl acetate | 200 ppm TWA 250 ppm STEL | 200 ppm (610 mg/m3) PEL | None | None |
| Solvent naphtha (petroleum), light aliphatic, low benzene content | None | None | None | None |
| Cyclohexane | 100 ppm TWA | 300 ppm (1,050 mg/m3) PEL | None | None |
| Propane | Included in the regulation but with no data values. See regulation for further details | 1,000 ppm (1,800 mg/m3) PEL | None | None |

Engineering controls: Provide local and general exhaust ventilation to effectively remove and

prevent buildup of any vapors or mists generated from the handling of this

product.

Respiratory protection: If ventilation is not sufficient to effectively prevent buildup of aerosols, mists or

vapors, appropriate NIOSH/MSHA respiratory protection must be provided.

Eye/face protection: Safety goggles or safety glasses with side shields.

Skin protection: Wear impervious gloves for prolonged contact. Use of impervious apron and

boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: aerosol Color: Off white Odor: Solvent Odor threshold: Not available. pH: Not applicable Vapor pressure: Not available. Boiling point/range: Not available. Melting point/ range: Not available. Specific gravity: 0.8300 - 0.8400 Vapor density: Not available. Flash point: Not available.

Flashback: This product exhibits flashback when tested for flame extension.

Flammable/Explosive limits - lower: Not available.
Flammable/Explosive limits - upper: Not available.
Autoignition temperature: Not available.

Flammability: The substance or mixture is a flammable aerosol with the category 2.

Evaporation rate: > 1 (Butyl acetate = 1)

Solubility in water: Insoluble Partition coefficient (n-octanol/water): Not available.

VOC content: 54.80 %; 307.77 g/l (by weight, calculated using CARB method; g/L less

water, less exempts calculated using SCAQMD method)

Viscosity: Not available. **Decomposition temperature:** Not available.

10. STABILITY AND REACTIVITY

Stability: Stable at normal conditions.

Hazardous reactions: Will not occur.

Hazardous decomposition

products:

IDH number: 1629134

Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low

molecular weight hydrocarbons. Oxides of nitrogen.

Incompatible materials: This product may react with strong acids, bases and oxidizing agents.

Reactivity: Not available.

Conditions to avoid: Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation: Inhalation of vapors or mists of the product may be irritating to the respiratory system.

Skin contact: This product may cause irritation to the skin.

Eye contact: This product is severely irritating to the eyes and may cause eye burns. Ingestion: Ingestion of this product may cause nausea, vomiting and diarrhea.

| Hazardous Component(s) | LD50s and LC50s | Immediate and Delayed Health Effects | |
|---|--|---|--|
| Acetone | Oral LD50 (Mouse) = 3,000 mg/kg Oral LD50 (Rabbit) = 5,340 mg/kg Oral LD50 (Rat) = 5,800 mg/kg Oral LD50 (Rat) = 9,800 mg/kg Oral LD50 (Mouse) = 5.2 g/kg Dermal LD50 (Rabbit) = 20,000 mg/kg Inhalation LC50 (Rat, 4 h) = 76 mg/l | Central nervous system, Irritant | |
| Methyl acetate | Oral LD50 (Rabbit) = 3.7 g/kg | Blood, Central nervous system, Eyes, Irritant | |
| Solvent naphtha (petroleum), light aliphatic, low benzene content | None | Irritant | |
| Cyclohexane | Oral LD50 (Rat) = 29,820 mg/kg Oral LD50 (Mouse) = 1,300 mg/kg | Irritant, Central nervous system | |
| Propane | None | Cardiac, Central nervous system, Irritant | |

| Hazardous Component(s) | NTP Carcinogen | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|---|----------------|-----------------|--|
| Acetone | No | No | No |
| Methyl acetate | No | No | No |
| Solvent naphtha (petroleum), light aliphatic, low benzene content | No | No | No |
| Cyclohexane | No | No | No |
| Propane | No | No | No |

12. ECOLOGICAL INFORMATION

Ecological information: Harmful to aquatic organisms.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

Hazardous waste number: If discarded, this product is considered a RCRA ignitable waste, D001. It is the

responsibility of the user to determine if an item is hazardous as defined in the Resource Conservation and Recovery Act (RCRA) at the time of disposal. Product uses, transformations, mixtures, processes, etc., may render the resulting material hazardous, under the criteria of ignitability, corrosivity, reactivity and toxicity characteristics of the Toxicity Characteristics Leaching

Procedure (TCLP) 40 CFR 261.20-24.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Aerosols
Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

DOT Hazardous Substance(s): Cyclohexane, Acetone

International Air Transportation (ICAO/IATA)

Proper shipping name: Aerosols, flammable

Hazard class or division: 2.1
Identification number: UN 1950
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: AEROSOLS (Cyclohexane)

Hazard class or division:

Identification number:

Packing group:

Marine pollutant:

2.1

UN 1950

None

Cyclohexane

15. REGULATORY INFORMATION

United States Regulatory Information

IDH number: 1629134

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act

Inventory.

TSCA 12 (b) Export Notification: None above reporting de minimis

CERCLA/SARA Section 302 EHS: None above reporting de minimis.

CERCLA/SARA Section 311/312: Immediate Health, Fire, Sudden Release

CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of

section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40

CFR 372). Cyclohexane (CAS# 110-82-7).

CERCLA Reportable quantity: Cyclohexane (CAS# 110-82-7) 1,000 lbs. (454 kg)

California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This

product contains a chemical known to the State of California to cause birth defects or other

reproductive harm.

Canada Regulatory Information

IDH number: 1629134

CEPA DSL/NDSL Status:

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Donna Houston, Regulatory Affairs Specialist

Issue date: 08/04/2016

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.