

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 31-Jul-2015

1. PRODUCT AND COMPANY IDENTIFICATION

<u>Product Identifier</u> Product Name: Product Number: Recommended Use: Uses Advised Against:	WOODFORCE MAINTAINER 5828 Dust cloth treatment For Industrial and Institutional Use Only
Manufacturer/Supplier:	Spartan Chemical Company, Inc. 1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com
24 Hour Emergency Phone Number Medical Emergency/Information: Transportation/Spill/Leak:	's: 888-314-6171 CHEMTREC 800-424-9300
	2. HAZARDS IDENTIFICATION
GHS Classification Serious Eye Damage/Eye Irritation:	Category 2A
GHS Label Elements Signal Word:	Warning
Symbols:	
Hazard Statements: Precautionary Statements:	Causes serious eye irritation
Prevention:	Wash hands and any exposed skin thoroughly after handling. Wear eye / face protection
Response: -Eyes	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
-Specific Treatment:	present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.
Storage: Disposal:	Not Applicable Not Applicable
Hazards Not Otherwise Classified:	Not Applicable
Other Information:	 May be harmful if swallowed. May cause skin irritation. Inhalation of vapors or mist may cause respiratory irritation. Keep out of reach of children.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
petroleum distillate	64742-46-7	1-5
ethylene glycol	107-21-1	1-5
alcohol ethoxylate	68131-39-5	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

-Eye Contact: -Skin Contact: -Inhalation: -Ingestion: Note to Physicians:	Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. Wash with soap and water. If skin irritation occurs: Get medical attention. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison control center or physician if you feel unwell. Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if you feel unwell. Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			
Suitable Extinguishing Media:	Product does not support combustion, Use extinguishing agent suitable for type of surrounding fire		
Specific Hazards Arising from the	Dried product is capable of burning. Combustion products are toxic.		
Chemical: Hazardous Combustion Products:	May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.		
Protective Equipment and Precautions for Firefighters:	Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full protective gear. Cool fire-exposed containers with water spray.		

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Environmental Precautions: Methods for Clean-Up:	Avoid contact with skin, eyes or clothing. Use personal protective equipment as required. Do not rinse spill onto the ground, into storm sewers or bodies of water. Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / patients (see Section 13)
	and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

Advice on Safe Handling:Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly
after handling.Storage Conditions:Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach
of children. Keep from freezing.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
ethylene glycol	Ceiling: 100 mg/m ³ aerosol only	(vacated) Ceiling: 50 ppm	-
107-21-1		(vacated) Ceiling: 125 mg/m ³	

Engineering Controls:

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other engineering controls should be considered.

Personal Protective Equipment	
Eye/Face Protection:	Wear splash goggles.
Skin and Body Protection:	Wear rubber or other chemical-resistant gloves.
Respiratory Protection:	Not required with expected use.
	If occupational exposure limits are exceeded or respiratory irritation occurs, use of a
	NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section
	3 should be considered.
General Hygiene Considerations:	Wash hands and any exposed skin thoroughly after handling.
	See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid
Color:	White emulsion
Odor:	Fresh
pH:	8.5-9.5
Melting Point / Freezing Point:	No information available.
Boiling Point / Boiling Range:	100 °C / 212 °F
Flash Point:	> 100 °C / > 212 °F ASTM D56
Evaporation Rate:	< 1 (Butyl acetate = 1)
Flammability (solid, gas)	No information available.
Upper Flammability Limit:	No information available.
Lower Flammability Limit:	No information available.
Vapor Pressure:	No information available.
Vapor Density:	No information available.
Specific Gravity:	1.00
Solubility(ies):	Miscible in water
Partition Coefficient:	No information available.
Autoignition Temperature:	No information available.
Decomposition Temperature:	No information available.
Viscosity:	No information available.

10. STABILITY AND REACTIVITY

Reactivity:	This material is considered to be non-reactive under normal conditions of use.
Chemical Stability:	Stable under normal conditions.
Possibility of Hazardous Reactions	: Not expected to occur with normal handling and storage.
Conditions to Avoid:	Extremes of temperature and direct sunlight.
Incompatible Materials:	Strong oxidizing agents. Strong acids.
Hazardous Decomposition	May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.
Products:	

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:	Eyes, Skin, Ingestion, Inhalation.		
Symptoms of Exposure:			
-Eye Contact:	Pain, redness, swelling of the conjunctiva and blurred vision.		
-Skin Contact:	Drying of the skin.		
-Inhalation:	Nasal discomfort and coughing.		
-Ingestion:	Pain, nausea, vomiting and diarrhea.		
Immediate, Delayed, Chronic Effects	- }		
Product Information:	Data not available or insufficient for classification.		
Target Organ Effects: Numerical Measures of Toxicity	Central nervous systemEyes. Respiratory SystemSkin.		
	ATE) are calculated based on the GHS document.		
ATEmix (oral): ATEmix (dermal):	13529 mg/kg 35962 mg/kg		

5828 - WOODFORCE MAINTAINER

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
petroleum distillate 64742-46-7	= 7400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 4.6 mg/L (Rat)4 h
ethylene glycol 107-21-1	= 4000 mg/kg (Rat)	= 9530 µL/kg (Rabbit)	Not Available
alcohol ethoxylate 68131-39-5	= 2 g/kg (Rat)	Not Available	Not Available

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
petroleum distillate 64742-46-7	Not Available	35: 96 h Pimephales promelas mg/L LC50 flow-through 10000: 96 h Pimephales promelas mg/L LC50 static	Not Available	Not Available
ethylene glycol 107-21-1	6500 - 13000: 96 h Pseudokirchneriella subcapitata mg/L EC50	41000: 96 h Oncorhynchus mykiss mg/L LC50 14 - 18: 96 h Oncorhynchus mykiss mL/L LC50 static 27540: 96 h Lepomis macrochirus mg/L LC50 static 40761: 96 h Oncorhynchus mykiss mg/L LC50 static 40000 - 60000: 96 h Pimephales promelas mg/L LC50 static 16000: 96 h Poecilia reticulata mg/L LC50 static	Not Available	46300: 48 h Daphnia magna mg/L EC50

Persistence and Degradability:	No informa
Bioaccumulation:	No informa

nation available. ation available.

Other Adverse Effects:

No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: Contaminated Packaging: Dispose of in accordance with federal, state and local regulations. Dispose of in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

<u>DOT:</u> Proper Shipping Name: Special Provisions:	Not Regulated Non Hazardous Product Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation expert for information specific to your situation.
IMDG:	Not Regulated
Proper Shipping Name:	Non Hazardous Product

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances: **ethylene glycol** CAS No 107-21-1

SARA 311/312 Hazard Categories	
Acute Health Hazard:	Yes
Chronic Health Hazard:	No
Fire Hazard:	No
Sudden release of pressure hazard:	No
Reactive Hazard:	No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION						
NFPA HMIS	Health Hazards: 1 Health Hazards: 1	Flammability: 0 Flammability: 0	Instability: 0 Physical Hazards: 0	Special: N/A		
Revision Date: Reasons for Revision:	31-Jul-2015 Section 14 and 15					

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet