J.P. Nissen Co. 2544 Fairhill Avenue P.O. Box 339 Glenside, PA 19038 Phone: 215-886-2025 Fax: 215-886-0707

Emergency: 1-800-424-9300

Material Safety Data Sheet January 5, 2011 Product Identification NISSEN FELTIP INK MARKER – ALL COLORS

HMIS Ratings- Health 1 Flammability 3 Reactivity 1
NFPA Ratings- Health 1 Flammability 3 Reactivity 0

Hazardous ingredients - The paint is contained in a valve action reservoir and will not leak under normal conditions.

 Ingredients
 CAS#
 %
 Exposure Limits

 1- Propanol
 71-23-8
 30-50
 200 PPM

 Ethyl Alcohol
 PM 4084
 64-17-5
 30-50
 1000 PPM

Physical Data

Boiling point: 207 degrees Vapor density: Heavier than air.

Volatile %:99% by volume **Specific gravity**: Less than 1.

Evaporation rate: Slower than Ethyl Ether Vapor Pressure: 14.9 mm hg @ 20 deg.c

Appearance: Thin Liquid

Volatile Organic Compound data not required because product only produced in quantities of less than 1 liter

Fire and Explosion Data

Flammability Class: IC Flashpoint: 76 deg.F LEL:1% UEL: 7%

Extinguishing Media: Foam, Carbon dioxide, or any Class B extinguishing agent. Water may be unsuitable as an extinguishing medium, but helpful in keeping adjacent containers cool.

Health Hazard Data

Listed as possible carcinogen: NTP - No IARC - OSHA - No

Symptoms of over exposure: Headache, Dizziness, Nausea, Coughing, Eye, Throat and Skin Irritation. **Effects of overexposure**: Slight to severe irritation to eyes and mucous membranes. Dermatitis.

Affects central nervous system.

Emergency first aid: Inhalation; seek fresh air. Give artificial respiration if not breathing.

Skin contact; Wash with soap and water. Ingestion; Call Physician. Do not induce vomiting. If vomiting occurs, keep head below hips to prevent aspiration of liquid into lungs

Reactivity Data

Stability: Stable, hazardous polymerization: Will not occur.

Conditions to avoid: Heat, open flames and sparks. **Incompatibility**: Do not expose to strong oxidizers.

Hazardous decomposition products: Carbon monoxide, carbon dioxide.

Environmental Protection Procedures

Remove all sources of ignition, ventilate area, and use absorbent material to clean spills. Disposal method: Dispose of waste in accordance with all local, state and federal regulations.

Control Measures

Respiratory protection: None required under normal use.

Ventilation: Normal-working conditions.

Protective Equipment: Safety glasses and gloves. No special clothing required under normal

conditions of use.

Transportation

Shipping Class ORM-D UN Number 1263 Package Group III

Toxic Substances Control Act (TSCA) States:

All components of this product are listed in the EPA's Inventory of Chemical Substances as required under the Toxic Substances Control Act (TSCA)

For more information visit: http://www.nissenmarkers.com/