Black Lead Page 1 of 3

May be used to comply wit	Material Safety Data Sheet				U.S. Department of Labor			
				Occupational Safety and Health Administration(Non-				
OSHA's Hazard Communication Standard			Mandatory Form)					
29 CFR 1910.1200. Standard must be			Form Approved					
consulted for specific requirements. IDENTITY (As used on Label and list) -			OMB No. 1218-0072 Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space					
							Pencil Lead	
(<i>PL5</i> , <i>PL7</i>)								
Black								
Section 1								
Manufacturer's Name			Telephone Number					
The Pilot Precision Co., LTD			+81-463-55-1230					
Address(Number, Street, C		Fax Number						
1667 Tamura Hiratsul		+81-463-55-1392						
T/ T 05.4	0012		Date Prepared	-				
Kanagawa, Japan 254-0013			September 25, 2007					
		Signature of Preparer(Optional)						
Section II - Hazardou	s Ingredients/I	dentity Info	rmation					
Hazardous Components(Specific Chemical Identity;			ommon Name(s))	OSHA	PEL ACGIH Other Limits % TLV Recommended (optional			
NAME	CAS. NO.	TLV(PPM)	WT. (%)		COMPONENT			
Graphite	7782-42-5		18					
Silicone Oil 63148-62-9			20					
Section III - Physical/	Chemical Char	acteristics						
Section III - Physical/ Boiling Point	Chemical Char	acteristics			Specific Gravity			
Boiling Point	Chemical Char	racteristics			Specific Gravity (H20=1) Melting Point			
Boiling Point	Chemical Char	racteristics			(H20=1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1)		racteristics			(H20=1) Melting Point Evaporation Rate (Butyl Acetate =			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1)	ble	acteristics			(H20=1) Melting Point Evaporation Rate (Butyl Acetate =			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i>	ble orless				(H20=1) Melting Point Evaporation Rate (Butyl Acetate =			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and	eble orless Explosion Haza	ard Data	mable Limits		(H20=1) Melting Point Evaporation Rate (Butyl Acetate =			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i>	oble orless Explosion Haza 260 dg C (Oil)	a rd Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>Foan</i>	oble orless Explosion Haza 260 dg C (Oil) n, dry chemical,	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used)	oble orless Explosion Haza 260 dg C (Oil) n, dry chemical,	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>Foan</i>	oble orless Explosion Haza 260 dg C (Oil) n, dry chemical,	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>Foan</i>	orless Explosion Haza 260 dg C (Oil) n, dry chemical dures Not require	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used) Extinguishing Media <i>Foar</i> Special Fire Fighting Proce Unusual Fire and Explosion	eble orless Explosion Haza 260 dg C (Oil) n, dry chemical, dures Not require	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			
Boiling Point Vapor Pressure(mm Hg) Vapor Density(Air=1) Solubility in Water <i>Insolu</i> Appearance and Odor <i>Od</i> Section IV - Fire and Flash Point(Method Used) A Extinguishing Media <i>Foar</i> Special Fire Fighting Proce	eble orless Explosion Haza 260 dg C (Oil) n, dry chemical, dures Not require	ard Data Flam			(H20=1) Melting Point Evaporation Rate (Butyl Acetate = 1)			

Black Lead Page 2 of 3

	Stable		X	
Incompatibility				
(Materials to Avoid)				
Hazardous Decomposition				
or Byproducts Hazardous Polymerization	May Occur			Condition to Avoid
riazaidous Polymenzadon				Colldition to Avoid
	May Not Occur			
Section VI - Health Ha	ızard Data			
Route(s) of Entry:	Inhalation? N/A	Skin?		Ingestion?
Health Hazards(Acute and C	hronic)			
Carcinogenicity:	NTP? None	IARC Monogr	raphs? <i>None</i>	OSHA Regulated? <i>None</i>
	WII II VOICE		T	OBITA Regulated 17 Vote
G' 1 G				
Signs and Symptoms of Exp	osure			
Medical Conditions				
Generally Aggravated by Ex	posure <i>N/A</i>			
Emergency and First Aid Pro	ocedures			
Ingestion: Wash out mouth				for at least 15 mins Skin:
Remove product from skin v			<i>t</i> .	
Section VII - Precaution	ons for Safe Handling	g and Use		
Steps to Be Taken in Case M	Iaterial is Released or Spil	led		
Remove black lead by v	acuum suction.			
Waste Disposal				
In accordance with nat	ional, state and local	regulations.		
			a in accord	lance with national, state
and local regulations.	Tanding and Storing AV	om rough nanding	g, in accord	ance with national, state
ana tocai regulations.				
Other Precautions				
Section VIII - Control	Measures			
Respiratory Protection(Speci				
Ventilation	Local Exhaus	st	Special	
	Mechanical(C		Other	
Protective Gloves		Eye Protection	ļ.	
Other Protective Clothing or	Equipment			
Work/Hygienic Practices				



Black Lead Page 3 of 3

RETURN TO DATA SHEET INDEX