

## **GENERAL PRODUCT SPECIFICATION**

Item No.	SW46				
Date	11-05-03	Replaces	5-30-02	No. Pages	1

Product Description:		
Style	SOC	
Item Size (each)	3"d x 42" long [end-to-end] **	
Color	Gray with black logo printing	
Composition	Corn Cob fill; Polypropylene	
Structure	Sorbent fill: Granular Corn Cob	
	Outer covering: Spunbond polypropylene nonwoven (15-30 micron dia. fiber)	
Technology	Sock filling + Spunbond + Tipper-Tie end closures	
Absorbency	Hydrophilic + Oleophilic	
Intended Application	Universal Sorbent Sock for Non-Aggressive Spills of Water Base, Oil Base, or	
	Solvent Base Liquids	
Absorbency Capacity	20 gal per case (saturated; medium viscosity-3x)	

## **Packaging Description:**

I dehaging Description.			
Package configuration	1-Case	Pkg. Weight	45 - 50 lb. (est.)
Items per Package	40 SOCS/Case	Pkg. Dimensions (approx.)	34" x 13.5" x 18.5" H
Container type	Carton w / Handle		

## **Physical Properties:**

Parameter	SPC Test Method	<u>Units</u>	Nominal	(+/-)Tolerance
SOC Weight (Estimate)	Gravimetric	lbs	1.1	0.2
SOC Fill	Packaged by volume	inches	fill height $= 36.5$	+ 1, - 2
Absorbency** (med.	SPCTM-012B	gL/gS	3	2.5-min.
oil)				
Color	Visual		Gray	per standard

The above properties are "nominal" values used for PROCESS CONTROL when the product is produced and/or inspected. Performance "nominals" may vary depending upon the specific application, and/or the environment being applied, stored, or shipped. \*\* The "Absorbency" Spec and "SPCTM012" test method is based on the protocol of ASTM F726, using SAE20 non-detergent as the Oil Type, medium viscosity.

Attributes	Product will be free of foreign material contamination, rips, holes, and tears.	
Labeling Each package to be clearly labeled with Company Name, Address, Item No.		
	Date, and/or Package Code (Bar Code).	
Certification	Make no changes in basic process or composition without notifying customer.	
	Claims for non-conformance of goods must be made within 60-days of delivery.	

645 Howard Avenue, Somerset, New Jersey 08873 ++ 732-302-0080 ++ 800-333-7672 ++ Fax 732-302-0969