

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 10-Aug-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name: CONCENTRATED WINDOW CLEANER

Product Number: 3060 ,3061 **Recommended Use:** Glass cleaner

Uses Advised Against: For Industrial and Institutional Use Only

Manufacturer/Supplier: Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak: CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Skin Corrosion/Irritation: Category 2
Serious Eye Damage/Eye Irritation: Category 2A
Flammable Liquids Category 3

GHS Label Elements

Signal Word: Warning Symbols:





Hazard Statements: Causes skin irritation.

Causes serious eye irritation Flammable liquid and vapor.

Precautionary Statements:

Prevention: Wash hands and any exposed skin thoroughly after handling.

Wear eye / face protection Wear protective gloves

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground container and receiving equipment. Use explosion-proof electrical equipment.

Use only non-sparking tools

Take precautionary measures against static discharge

Response:

-Skin

-Eyes IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

or shower. If skin irritation occurs: Get medical attention. Wash contaminated clothing

before reuse.

-Specific Treatment: See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

In case of fire: Use CO2, dry chemical, or foam for extinction Fire:

Store in a well-ventilated place. Keep cool Storage:

Dispose of contents and container in accordance with local, state and federal regulations. Disposal:

Hazards Not Otherwise Classified: Not Applicable

Other Information: · May be harmful if swallowed.

• Inhalation of vapors or mist may cause respiratory irritation.

· Keep out of reach of children.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
water	7732-18-5	60-100
isopropanol	67-63-0	10-30
acetic acid	64-19-7	1-5

Specific chemical identity and/or exact percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and -Eye Contact:

easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin -Skin Contact:

irritation occurs: Get medical attention. Wash contaminated clothing before reuse.

Revision Date: 10-Aug-2015

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a -Inhalation:

poison control center or physician if you feel unwell.

Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to an unconscious -Ingestion:

person. Get medical attention if you feel unwell.

Treat symptomatically. Note to Physicians:

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media: CO2, dry chemical, dry sand, alcohol-resistant foam, Move containers from fire area if you

can do it without risk

Specific Hazards Arising from the

Chemical:

flammable. Vapors may travel to source of ignition and flash back. Most vapors are heavier

than air. They will spread along ground and collect in low or confined areas (sewers,

basements, tanks).

Hazardous Combustion Products: May include Carbon monoxide Carbon dioxide and other toxic gases or vapors.

Protective Equipment and Precautions for Firefighters: Wear MSHA/NIOSH approved self-contained breathing apparatus (SCBA) and full

protective gear. Cool fire-exposed containers with water spray.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Remove all sources of ignition. Use personal protective equipment as required. Stop leak if

you can do it without risk. All equipment used when handling the product must be

grounded.

Environmental Precautions:

Methods for Clean-Up:

Do not rinse spill onto the ground, into storm sewers or bodies of water.

Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

7. HANDLING AND STORAGE

•

Advice on Safe Handling: Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly

after handling.

Storage Conditions: Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits:

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
isopropanol	STEL: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm
67-63-0	TWA: 200 ppm	TWA: 980 mg/m ³	TWA: 400 ppm
		(vacated) TWA: 400 ppm	TWA: 980 mg/m ³
		(vacated) TWA: 980 mg/m ³	STEL: 500 ppm
		(vacated) STEL: 500 ppm	STEL: 1225 mg/m ³
		(vacated) STEL: 1225 mg/m ³	
acetic acid	STEL: 15 ppm	TWA: 10 ppm	IDLH: 50 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m ³	TWA: 10 ppm
		(vacated) TWA: 10 ppm	TWA: 25 mg/m ³
		(vacated) TWA: 25 mg/m ³	STEL: 15 ppm
			STEL: 37 mg/m ³

Engineering Controls: Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

Revision Date: 10-Aug-2015

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Wear splash goggles.

Skin and Body Protection: Wear rubber or other chemical-resistant gloves.

Respiratory Protection: Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations: Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Liquid	
Color:	Light blue	
Odor:	Floral fragrance	
pH:	2.0-3.0	
Melting Point / Freezing Point:	No information available.	
Boiling Point / Boiling Range:	94 °C / 201 °F	
Flash Point:	30 °C / 86 °F ASTM D56	
Evaporation Rate:	< 1 (Butyl acetate = 1)	
Flammability (solid, gas)	No information available.	
Upper Flammability Limit:	No information available.	
Lower Flammability Limit:	No information available.	
Vapor Pressure:	No information available.	
Vapor Density:	No information available.	
Specific Gravity:	0.97	
Solubility(ies):	Soluble in water	
Partition Coefficient:	No information available.	
Autoignition Temperature:	No information available.	
Decomposition Temperature:	No information available.	
Viscosity:	No information available.	

10. STABILITY AND REACTIVITY

Revision Date: 10-Aug-2015

Reactivity: This material is considered to be non-reactive under normal conditions of use.

Chemical Stability: Stable under normal conditions.

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Heat, flames and sparks. Extremes of temperature and direct sunlight. Take precautionary **Conditions to Avoid:**

measures against static discharges.

Strong oxidizing agents. Strong acids. **Incompatible Materials:**

Hazardous Decomposition

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Products:

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure: Eyes, Skin, Ingestion, Inhalation.

Symptoms of Exposure:

-Eve Contact: Pain, redness, swelling of the conjunctiva and blurred vision.

-Skin Contact: Pain, redness and cracking of the skin. Nasal discomfort and coughing. -Inhalation: -Ingestion: Pain, nausea, vomiting and diarrhea.

Immediate, Delayed, Chronic Effects

Product Information: Data not available or insufficient for classification.

Target Organ Effects: -Eyes. Respiratory System. -Skin. Teeth.

Numerical Measures of Toxicity

The following acute toxicity estimates (ATE) are calculated based on the GHS document.

ATEmix (oral): 18336 mg/kg ATEmix (dermal): 22764 mg/kg ATEmix (inhalation-dust/mist): 185.7 mg/l

Component Acute Toxicity Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
water 7732-18-5	> 90 mL/kg (Rat)	Not Available	Not Available
isopropanol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870 mg/kg (Rabbit)	= 72.6 mg/L (Rat)4 h
acetic acid 64-19-7	= 3310 mg/kg (Rat)	= 1060 mg/kg (Rabbit)	= 11.4 mg/L (Rat) 4 h

Carcinogenicity: No components present at 0.1% or greater are listed as to being carcinogens by ACGIH, IARC, NTP or OSHA.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical Name	Algae/Aquatic Plants	Fish	Toxicity to Microorganisms	Crustacea
isopropanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50	Not Available	13299: 48 h Daphnia magna mg/L EC50
acetic acid 64-19-7	Not Available	79: 96 h Pimephales promelas mg/L LC50 static 75: 96 h Lepomis macrochirus mg/L LC50 static	Not Available	47: 24 h Daphnia magna mg/L EC50 65: 48 h Daphnia magna mg/L EC50 Static

No information available. Persistence and Degradability: Bioaccumulation: No information available. Other Adverse Effects: No information available.

13. DISPOSAL CONSIDERATIONS

Disposal of Wastes: This material, as supplied, is a hazardous waste according to federal regulations (40 CFR

261).

Contaminated Packaging: Dispose of in accordance with federal, state and local regulations.

US EPA Waste Number: D001

14. TRANSPORT INFORMATION

DOT:

UN/ID No: UN1993

Proper Shipping Name: Flammable liquids, n.o.s., (contains isopropanol)

Hazard Class: 3
Packing Group: III

Special Provisions: Class 3, Packing Group III materials meet the exception requirements of section 49 CFR

173.150 when individual containers of not more than 1.3 gallons are packed in a strong outer packaging and ground transportation is utilized. Such containers may be reclassified

Revision Date: 10-Aug-2015

as "Limited Quantity".

Shipping descriptions may vary based on mode of transport, quantities, package size, and/or origin and destination. Check with a trained hazardous materials transportation

expert for information specific to your situation.

IMDG:

UN/ID No: UN1993

Proper Shipping Name: Flammable liquids, n.o.s., (contains isopropanol)

Hazard Class: 3
Packing Group: III

15. REGULATORY INFORMATION

TSCA Status: (Toxic Substance Control Act Section 8(b) Inventory)

All chemical substances in this product are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

SARA 313

This product contains the following listed substances:

isopropanol

CAS No 67-63-0 only if manufactured by the strong acid process, no supplier notification

SARA 311/312 Hazard Categories

Acute Health Hazard:

Chronic Health Hazard:

No
Fire Hazard:

Sudden release of pressure hazard:

No
Reactive Hazard:

No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA Health Hazards: 2 Flammability: 3 Instability: 0 Special: N/A

HMIS Health Hazards: 2 Flammability: 3 Physical Hazards: 0

Revision Date: 10-Aug-2015 Reasons for Revision: Section 14 and 15

Revision Date: 10-Aug-2015

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet